

#### **TECH OFFER**

### Adsorbent for Low Concentration & Room Temperature Adsorption of Carbon Dioxide



### **KEY INFORMATION**

TECHNOLOGY CATEGORY: Environment, Clean Air & Water - Filter Membrane & Absorption Material Green Building - Heating, Ventilation & Air-conditioning Materials - Plastics & Elastomers TECHNOLOGY READINESS LEVEL (TRL): TRL4 COUNTRY: SINGAPORE ID NUMBER: TO174739

## OVERVIEW

In recent years, there has been an increasing demand for carbon dioxide  $(CO_2)$  adsorbents due to climate change. These materials can be used for  $CO_2$  capture in both flue gas and directly from the air which can mitigate and reduce greenhouse gas (GHG) emissions. The current conventional  $CO_2$  adsorbents includes alkaline salts, aqueous amine solution and metal organic frameworks (MOF). However, these materials are expensive (MOF) and suffers from problems such as heat generation (alkaline salt) to energy intensive post-adsorption recovery (aqueous amine solution) which severely limits its wide scale adoption.

This technology offer is an amino-based resin adsorbent for low concentration and ambient temperature  $CO_2$  adsorption and desorption. This adsorbent is capable of adsorbing low concentrations of  $CO_2$  in air at room temperature and generates little heat when adsorbing  $CO_2$ . It is also possible to capture  $CO_2$  from flue gas in the same manner as well. In addition, the regeneration (release of  $CO_2$ ) of the adsorbent can be performed at low temperature with significantly less energy consumption than existing

For more information, contact techscout@ipi-singapore.org



materials.

# **TECHNOLOGY FEATURES & SPECIFICATIONS**

This technology offer is an amino-based resin adsorbent for low concentration and room temperature capture of CO<sub>2</sub>. The technical features and specifications are as follows:

- Porous amino-based resin
- Easy to handle granules
- High affinity CO<sub>2</sub> chemisorption
- Low concentration and temperature CO<sub>2</sub> adsorption (as low as 400 ppm and at room temperature)
- Desorption is possible at lower temperatures than existing materials (30 °C or higher)
- Environmentally friendly (non-toxic, non-volatile)
- Flexible implementation design (filter parts, filing columns etc.)

### POTENTIAL APPLICATIONS

The use of this technology is for industries who are interested in CO<sub>2</sub> capture and/or utilisation. The potential applications are:

- Scenarios for CO<sub>2</sub>Capture
  - Air conditioners (passive CO<sub>2</sub> capture and indoor CO<sub>2</sub> concentration control)
  - Manufacturing and other CO<sub>2</sub> emitting industries (removal of CO<sub>2</sub> from pre-combustion or flue gas)
- Scenarios for CO<sub>2</sub> Utilisation
  - Beauty applications (promotion of blood circulation by use of CO<sub>2</sub>)
  - Agriculture application (promotion of growth by use of CO<sub>2</sub>)

### UNIQUE VALUE PROPOSITION

- Low concentration and room temperature CO<sub>2</sub> capture
- Desorption is possible at lower temperatures than existing materials (30 °C or higher)
- Environmentally friendly adsorbent (non-toxic, non-volatile)
- Flexible use case (direct air capture, flue gas capture)

This technology owner is keen to out-license this patented technology, or to do R&D collaboration utilising the adsorbent material with partners who are interested in  $CO_2$  capture and/or utilisation.